


DVW 205

Zoom Profile Spotlight with Condenser Optics
30 - 54° 2000 W



ADB
A Siemens Company

DE 5650

The DVW 205 belongs to ADB's EUROPE range of professional theatre spotlights intended to fulfil the requirements of the most demanding Lighting Designers.

Designed around a 2000 W tungsten halogen lamp, this variable angle profile spotlight provides a high intensity, sharp edge, wide beam from very short distance over a useful range of 30°- 54°.

A PC like soft edge beam can be obtained through the insertion in the zoom of a glass diffuser (option).

The DVW 205 will yield 2,000 Lux at 8 m and still 1,000 Lux at 11 m.

The use of special optical glass with anti-reflection coating in addition to high performance, 2-lens condenser optics results in a spectacular high light output, an even light distribution and a unique beam edge sharpness.

Zoom focusing is smooth and stable in any position, and allows very accurate beam control.

Beam shaping and imaging are achieved comfortably by 4 shutters working in 2 planes, an iris diaphragm and a size A gobo.

A front cassette allows one-hand insertion of a colour frame.

The DVW 205 is rebalanceable in any position by sliding the yoke along 2 slots provided over the full length of the unit. The tiltlock mechanism is efficient and comfortable. The yoke can be adjusted to a low or high position, a useful facility when space is limited.


The lamp house which contains the shutter set and the effects slot is rotatable through 360° with respect to the lens tube and vice-versa. Depending on the yoke position, the operator can either rotate the projected image, or move the focus controls to a preferred position, or correct the lamp position back to the vertical when the spotlight is mounted on a sloping bar.

Professional mechanical design, rugged and modular construction from injected and extruded aluminium, anti-corrosion treatment of all metal components and high quality finish guarantee reliable operation over a very long lifetime.

In addition to meeting current international safety standards, this spotlight is equipped with several safety features which make it very safe to operate.

The standard unit is fitted with a 2 m silicone rubber power cable with open ends, 4 beam shaping shutters and a metal colour frame.

Options: pole operation, motorization.



Dimensions (A x B x C) = 700 x 420 x 500 mm

Net weight = 21.3 kg

Packing = 835 x 450 x 370 mm

Gross weight = 25.8 kg

9 units per pallet

DVW 205

Specifications

Housing

- The housing is built in 2 sections:
 - The lens tube fitted with a front cassette which provides 2 sets of runners for one-hand insertion of 245 x 245 mm (DIN 15560) accessories. The cassette is designed for preventing light spill.
 - The lamp house equipped with a spring-loaded 4-shutter gate assembly and extended runners for a drop-in iris diaphragm and a gobo-holder
- The lens tube and the lamp house are fitted with sliding lids for easy access to lenses and lamp.
- The lamp house is rotatable through 360° with respect to the lens tube and vice-versa. Effective clamping without any tool. A click-stop detent helps finding the normal position.
- The shutter gate contains 4 removable, stainless steel beam shaping shutters with anti-reflection coating, working in 2 planes.
- The back-end plate is fitted with a strong grab handle and CEE 22 power connector.
- Front cassette and back-end plate of injected aluminium. Main body of extruded aluminium sections.

Positioning Mechanism

- A strong steel yoke, with positive titlock mechanism on both sides, can slide along 2 slots provided over the full length of the housing to allow spotlight balance in any position. Clamping is by one clutch type handle which do not interfere with the shutters.
- 2 sets of holes in the yoke arms to allow high or low positioning of the spotlight.
- 5 holes in the transverse arm of the yoke for fixing on a hook clamp or a DIN 15560 plate.

Optical System

- Double spherical reflector of pure, polished, anodised aluminium.
- Aspherical condenser lens.
- Intermediary spherical lens.
- 30 - 54° zoom optics consisting of 4 polished plano-convex lenses.
- All lenses with anti-reflection coating.
- Optional zoom glass diffuser for sharp to soft edge beam conversion.
- Focusing mechanism with smooth control by 2 screw knobs.

Electromechanical Components

- 2 m silicone power cable with CEE 22 female connector on one end (luminaire side).
- GY 16 lampholder for 220/240 V, 2000 W tungsten halogen lamps with 70 mm light centre length (LCL).
- Very low noise axial fan

Safety / Reliability

- This equipment complies with all applicable European directives and carries a CE mark.
- A safety mechanism prevents access to the lamp without first disconnecting the power cable.
- The power connector is secured by a stirrup.
- The spotlight does not present any sharp edge.
- An anchorage ring is provided for safety bond.
- Spring lock mechanisms prevent accidental drop-out of accessories.
- All handles and control knobs are heat insulated.
- All metal parts are protected against corrosion.
- Overall finish in non-reflective, heat and wear resisting black paint

Lamps

- Life exp. (h) 400
- Colour Temperature (K) 3200

ADB - Your Partner for Light

Belgium	N.V. ADB S.A.	(Group Headquarters) Leuvensesteenweg 585, B-1930 Zaventem Tel : +32 / 2 / 722.17.11, Fax : +32 / 2 / 722.17.64 - e-mail : adb-ttv @ p1.bru1.siemens.be
Deutschland	ADB GmbH	Dieselstraße 4, D-63.165 Mühlheim am Main Tel : 06108 / 66204, Fax : 06108 / 66205 Büro Nord : Tel : 05331 / 469329, Fax : 05331 / 469177 • Büro Ost : Tel : 030 / 670 44 201, Fax : 030 / 670 44 200 • Büro Süd-West : Tel : 06509 / 8570, Fax : 06509 / 8560
France	ADB S.A.	rue de la Vanne 47, F-92120 Montrouge / Paris, Tel : 1 / 41.17.48.50, Fax : 1 / 42.53.54.76
Great Britain	LSI	Siemens House, D Block, Windmill Road, Sunbury-on-Thames, Middlesex TW 16 7HS Tel : 01932 / 75.28.85, Fax : 01932 / 75.28.83


Photometric Data

(Typical Values)

Lamp : 220V, 3200K, biplane **2000 W / 52,000 lm**

Minimum Angle : 30°

Throw distance (m)	2.5	5	7.5	10	12.5	15	17.5	20
Beam Ø (m)	1.3	2.7	4	5.4	6	8	9.4	10.7
Light level (lux)	20480	5120	2280	1280	820	570	420	320



Maximum Angle : 54°

Throw distance (m)	2.5	5	7.5	10	12.5	15	17.5	20
Beam Ø (m)	2.6	5.1	7.6	10.2	12.7	15.3	17.8	20.4
Light level (lux)	8480	2120	940	530	340	240	170	130

Accessories

- Set of 4 cardboard filter frames (245 x 245 mm)
- Metal filter frame (245 x 245 mm)
- Wiremesh safety guard (245 x 245 mm)
- Gobo holder for gobo A with retention ring
- Gobo holder for gobo B
- Gobo A - Ø 100 mm
- Gobo B - Ø 85 mm
- Iris diaphragm Ø 75 mm
- Iris diaphragm Ø 80 mm
- Iris diaphragm Ø 80 mm with black-out
- Suspension hook Ø 35 à 50 mm
- Suspension hook Ø 35 à 50 mm
- Suspension hook Ø 45 à 60 mm
- Safety chain 1.2 m
- Safety cable 1.2 m
- Light beam cone
- Glass diffuser 98 x 98 - for gobo holder type A
- Glass diffuser 120 x 120 - for zoom

PFC/245
PFM/245
GR/245
SP/GO/A
SP/GO/B
GO/A
GO/B
OR/75
OR/80
OR/80/BO
A20
A25
A30
CHAS 120
CAS 120
CL2
VD/98
VD/120

Subject to modifications

ADB
A Siemens Company